

How to Order

See "How To Order - Reference Table" on Previous Page for All Codes
Select your requirements and email the form to: quotes@cowandynamics.com



Example: Single Acting Spring-return

Pre-selected based on Torque See Torque Chart

Size: D01 (5000-25000 lbs-inch) | Scotch Yoke Module

Size: 6 | AS CAN #

Size: 2 | Hydraulic Actuator

Clockwise | Fail Rotation

Fail rotation (Loss of power) | Fail rotation (Loss of ESD signal) | Fail Function

Standard - (-20C to +40C) | Operational temperature rating

General purposes (CSA/CUL) | Hazardous Area Class

240VAC/1 Phase/60 HZ | Power Supply Voltage

E2H-ESD 1 A D 1 0 S G A 0 H A X I14 M P 0 0

Specials | Special configuration: None

Panel Orientation | Standard- Front- Hydraulic side

Partial Stroke | Yes

Manual Override | Hydraulic hand pump

Mounting | F14

Environmental Protection | NEMA 4X/IP66- Corrosion resistant

Communication | 4-20 mA PST

Interface | Smart* HMI-Multi Color Touch Screen

Control Panel | Standard

Final Part Number Order Example: E2H-ESD1AD10SGA0HAXI14MP00

Single Acting with Accumulators

Pre-selected based on Torque See Torque Chart

Size: D06 (450K-950K lbs-inch) | Scotch Yoke Module

Accumulator

Size: 2 | Hydraulic Actuator

Clockwise | Fail Rotation

Fail rotation (Loss of power) | Fail rotation (Loss of ESD signal) | Fail Function

Standard - (-20C to +40C) | Operational temperature rating

General purposes (CSA/CUL) | Hazardous Area Class

240VAC/1 Phase/60 HZ | Power Supply Voltage

E2H-ESD 6 A C P 1 0 S G A 0 H A X I40 M P 0 0

Specials | Special configuration: None

Panel Orientation | Standard- Front- Hydraulic side

Partial Stroke | Yes

Manual Override | Hydraulic hand pump

Mounting | F40

Environmental Protection | NEMA 4X/IP66- Corrosion resistant

Communication | 4-20 mA PST

Interface | Smart* HMI-Multi Color Touch Screen

Control Panel | Standard

Final Part Number Order Example: E2H-ESD6ACP10SGA0HAXI40MP00